

**TECH SPECS**

PHOTOMETRIC SPECIFICATIONS

**PHOTOMETRIC SPECIFICATIONS**

SERIES	KELVIN	CCT (K)	CRI	F.C./ LUX @12" (SIZE)	F.C./ LUX @24" (SIZE)	F.C./ LUX 36" (SIZE)	F.C./ LUX @48" (SIZE)	F.C./ LUX @5' (SIZE)	F.C./ LUX @6' (SIZE)
2' X 4'	Tungsten	2675	95	1030.9 fc/ 11097 lux	577.4 fc/ 6215 lux	331.7 fc/ 3571 lux	208.4 fc/ 2243 lux	141.8 fc/ 1527 lux	99.6 fc/ 1072 lux
	Daylight	6010k	95	1168 fc/ 12572 lux	659.2 fc/ 7096 lux	375.1 fc/ 4038 lux	238.8 fc/ 2570 lux	162 fc/ 1743 lux	114.4 fc/ 1232 lux
	Hybrid	4053K	95	1163.8 fc/ 12527 lux	640 fc/ 6888 lux	369.9 fc/ 3982 lux	229.5 fc/ 2470 lux	157.9 fc/ 1699 lux	113.2 fc/ 1218 lux

**MECHANICAL AND ELECTRICAL SPECIFICATIONS**

SERIES	HEIGHT (INCH)	HEIGHT (MM)	WIDTH (INCH)	WIDTH (MM)	DEPTH (INCH)	DEPTH (MM)	WEIGHT (LBS)	VOLTAGE (V DC)	CURRENT (AMPS)	DRAW @ 120V	WATTS	LED QTY
2' X 4'	24.75	628.65	43	1092.2	1	25.4	2	24	11	1.8A	230	1800

