

The Aladdin A-LITE is a high-end variable bi-color on-board LED light with an integrated battery. The light quality of the Aladdin A-LITE is outstanding with CRI and TLCI ratings of over 97 for both tungsten and daylight. The integrated lithium-ion battery has a runtime of 1 hour and 20 minutes at full power and can be charged quickly via the included Micro USB-to-USB cable. This USB cable allows you to power and/or charge the A-LITE from any USB charger, laptop, camera or battery with a USB port. The A-LITE is the slimmest and lightest on-board light on the market and the housing is made from aircraft-grade aluminum. The light comes with a standard 1/4-20" thread to mount to any on-board adapter. A removable hinged, plastic diffuser is included with the light to soften the light even further. The A-LITE produces a color temperature range from tungsten (2900°K) to daylight (6300°K) and every point in between, and is completely dimmable from 5–100%.

In the box: 1x A-Lite - 1x Diffusion filter - 1x USB cable

- Light Source: Super high CRI Power LED's (8W)
- Beam Angle: 140°
- Driver: Flicker-Free by CC driver (efficiency>93%)
- Switch: (ON/OFF)
- Dimmer: Dimming: (5%–100%)
- color temperatur control: 2900°K–6300°K
- Battery: 3,7V 2,5A Li-ion battery
- Housing: material Aluminium 6061 T6 (Aircraft grade)
- Cooling: passive cooling
- Dimension: 156 x 80 x 11,5mm
- Weight: 205g
- Power input: Micro USB 3,6V
- Mounting: 1/4 Screw

CRI	Daylight	97
	Bi-Color	97
	Tungsten	97
TLCI	Daylight	98
	Bi-Color	98
	Tungsten	98
Lux Tungsten to Daylight	60cm / 2ft	556-589 lux
	1m / 3,3ft	200-216 lux
	2m / 6,6ft	55-59 lux
	3m / 9,9ft	27-28 lux
Color temperature	Daylight	6300°K
	Tungsten	2900°K