

TECH SPECS

PHOTOMETRIC SPECIFICATIONS

SERIES	KELVIN	CCT (K)	CRI	F.C./ LUX @12" (SIZE)	F.C./ LUX @24" (SIZE)	F.C./ LUX 36" (SIZE)	F.C./ LUX @48" (SIZE)	F.C./ LUX @5' (SIZE)	F.C./ LUX @6' (SIZE)
4' X 4'	<i>Tungsten</i>	2675	95	1329.4 fc/ 14309 lux	920.4 fc/ 9907 lux	578.9 fc/ 6232 lux	379.6 fc/ 4086 lux	267.6 fc/ 2881 lux	192.9 fc/ 2077 lux
	<i>Daylight</i>	6010k	95	1510.3 fc/ 16256 lux	1035.1 fc/ 11142 lux	651.2 fc/ 7 7009 lux	430.3 fc/ 4632 lux	301.1 fc/ 3241 lux	301.1 fc/ 3241 lux
	<i>Hybrid</i>	4053K	95	1464.2 fc/ 15761 lux	953.7 fc/ 10265 lux	600.9 fc/ 6468 lux	399.6 fc/ 4301 lux	282.6 fc/ 3042 lux	207.6 fc/ 2235 lux

MECHANICAL AND ELECTRICAL SPECIFICATIONS

SERIES	HEIGHT (INCH)	HEIGHT (MM)	WIDTH (INCH)	WIDTH (MM)	DEPTH (INCH)	DEPTH (MM)	WEIGHT (LBS)	VOLTAGE (V DC)	CURRENT (AMPS)	DRAW @ 120V	WATTS	LED QTY
4' X 4'	46.75	1187.45	42.75	1085.85	0.9	23	4.5	24	22	3.5A	460	3600

