



**KINO FLO**<sup>®</sup>  
Lighting Systems

# celeb<sup>®</sup> 400

LED



# Celeb® 400 DMX LED



The Celeb® 400 DMX joins Kino Flo's line of LED lighting systems. With soft, even True Match® light quality (CRI 95), the Celeb 400 boasts technical innovations that make it an ideal professional imaging tool: dial-in white light from 2700 to 5500 Kelvin and presets with programmable settings. Light levels do not change when selecting Kelvin settings. The Celeb also includes full range dimming without color shift.

The Celeb 400 DMX operates at universal input from 100VAC-240VAC or battery power. The slim profile fixture produces more lumens than a 1K tungsten softlight, yet uses only 1.8A (120VAC) compared to a tungsten softlight at 8.3A. The Celeb comes with molded accessory holders, removable gel frame and focusing louver.

Features include:

- Kelvin presets and custom settings between 2700-5500K
- Universal input 100VAC-240VAC or 24VDC
- Onboard and DMX dimming
- Flicker-free, dead quiet operation
- Gel Frame and Honeycomb Louver
- Center Mount, Yoke Mount and Pole-Op

## ▼ Celeb 400 DMX LED Center



**CEL-400C-120U**  
Celeb 400 DMX  
Center Mount, Univ 120U

**CEL-400C-230U**  
Celeb 400 DMX  
Center Mount, Univ 230U



**GFR-CE4**  
Celeb 400 Gel Frame  
(Included)



**LVR-CE490-P**  
Celeb 400 Louver/HP, 90°  
(Included)



**MTPLM**  
Kino 81 Lollipop w/  
Junior Pin (28mm)  
(Included)

## ▼ Celeb 400 DMX LED Yoke



**CEL-400Y-120U**  
Celeb 400 DMX  
Yoke Mount, Univ 120U

**CEL-400Y-230U**  
Celeb 400 DMX  
Yoke Mount, Univ 230U



**CEL-400P-120U**  
Celeb 400 DMX  
Pole-Op, Univ 120U

**CEL-400P-230U**  
Celeb 400 DMX  
Pole-Op, Univ 230U



**GFR-CE4**  
Celeb 400 Gel Frame  
(Included)



**LVR-CE490-P**  
Celeb 400 Louver/HP, 90°  
(Included)

▼ Photometrics

|                  |        |      |      |      |     |     |     |     |     |     |     |
|------------------|--------|------|------|------|-----|-----|-----|-----|-----|-----|-----|
|                  | FC     | 687  | 220  | 105  | 61  | 40  | 28  | 21  | 16  | 13  | 11  |
|                  | Feet   | 2    | 4    | 6    | 8   | 10  | 12  | 14  | 16  | 18  | 20  |
| <b>Celeb 400</b> | LUX    | 9800 | 3423 | 1647 | 958 | 634 | 442 | 331 | 258 | 208 | 168 |
|                  | Meters | 0.5  | 1    | 1.5  | 2   | 2.5 | 3   | 3.5 | 4   | 4.5 | 5   |

▼ Fixture Specifications

| Fixture                     | Input Voltage VAC         | Amps VAC | Input Voltage VDC | Amps VDC | Kelvin Range | Dimming Range | Dimensions                       | Weight       |
|-----------------------------|---------------------------|----------|-------------------|----------|--------------|---------------|----------------------------------|--------------|
| <b>Celeb 400 DMX Center</b> | 100-240VAC, 50/60Hz, 210W | 1.8A     | 18-28VDC, 198W    | 8.25A    | 2700-5500    | 100%-1%       | 45 x 14 x 5" (114.5 x 36 x 13cm) | 26 lb (12kg) |
| <b>Celeb 400 DMX Center</b> | 240-100VAC, 50/60Hz, 207W | 1.0A     | 18-28VDC, 198W    | 8.25A    | 2700-5500    | 100%-1%       | 45 x 14 x 5" (114.5 x 36 x 13cm) | 26 lb (12kg) |
| <b>Celeb 400 DMX Yoke</b>   | 100-240VAC, 50/60Hz, 210W | 1.8A     | 18-28VDC, 198W    | 8.25A    | 2700-5500    | 100%-1%       | 50 x 16.5 x 5" (127 x 42 x 13cm) | 26 lb (12kg) |
| <b>Celeb 400 DMX Yoke</b>   | 240-100VAC, 50/60Hz, 207W | 1.0A     | 18-28VDC, 198W    | 8.25A    | 2700-5500    | 100%-1%       | 50 x 16.5 x 5" (127 x 42 x 13cm) | 26 lb (12kg) |

▼ Details



Bill Roe



Bill Roe



Bill Roe

▼ Celeb 400 DMX LED Kits



**KIF-C4-120U**  
Celeb 400 DMX Center Mount Kit, Univ 120U

**KIF-C4-230U**  
Celeb 400 DMX Center Mount Kit, Univ 230U

**Contents**  
1 Celeb 400 DMX Center  
1 Flight Case

**Dimensions**  
53.5 x 11 x 16.5"  
(136 x 28 x 42cm)  
**Weight**  
52.5 lb (24kg)




**KIF-C4Y-120U**  
Celeb 400 DMX Yoke Mount Kit, Univ 120U

**KIF-C4Y-230U**  
Celeb 400 DMX Yoke Mount Kit, Univ 230U


**Contents**  
1 Celeb 400 DMX Yoke  
1 Jr. Pin  
1 Ship Case

**Dimensions**  
53.5 x 9 x 23.5"  
(136 x 23 x 60cm)  
**Weight**  
53 lb (24kg)

▼ Celeb 400 DMX LED Accessories/ Cases



**BRD-CE4**  
Celeb 400 Barndoors  
(Set of 4)



**LVR-CE460-P**  
Celeb 400 Louver/HP, 60°



**MTP-180**  
Junior Pin Assembly  
for Yoke (28mm)



**MTP-CE**  
Celeb Support w/ Pin



**7010045**  
Celeb 400  
Yoke Assembly



**7010046**  
Celeb 400  
Pole-Op Assembly



**KAS-CE4**  
Celeb 400 Center Flight Case



**KAS-CE4-C**  
Celeb 400 Center Travel Case



**KAS-CE4-S**  
Celeb 400 Center Ship Case

**KAS-CE4-Y**  
Celeb 400 Yoke Ship Case



**Kino Flo Lighting Systems**  
**2840 North Hollywood Way**  
**Burbank, CA 91505**

+1 818 767 6528 voice +1 818 767 7517 fax

[www.kinoflo.com](http://www.kinoflo.com)

© Kino Flo Celeb 400 DMX LED  
No. 3110079