



Specifications: CINETAPE MEASURE CONTROL

Size:	Inch: 3.0 x 3.0 x 1.2 mm: 76 x 76 x 31
Weight:	7 oz. (195 Grams)
Construction:	Machined Aluminum (Not Cast)
Finish:	Black Anodize, Engraved
Measurement Units:	Feet & Inches or Meters & Centimeters
Measurement Resolution:	1 inch; 1 cm
Film Plane Offset Range:	-9 to 99 ft; -3 to 30 m
Close Focus Range:	12 to 30 inch; 30 to 90 cm
Sensitivity Range:	0 to 99 %
Sensitivity Adjustment:	5 % Increments
Select / Adjust Switch:	Red Knob
FT-in / M-cm Switch:	Toggle
Power Connector:	Fischer 3 Pin
Sensor Connector:	Fischer 5 Pin
Remote Connector:	Lemo 6 Pin
Numeric Display:	Bright Red LED
Sense Indicator:	Bright Green LED
Film-Plane Adjust Indicator:	Bright Yellow LED
Sensitivity Adjust Indicator:	Bright Yellow LED
Circuit Protection:	Auto Reset Fuse
DC Power Requirements:	9 to 32 Volts
Current Consumption:	50 to 150 mA
Mounting:	Velcro

Specifications: SENSOR ASSEMBLY

Size:	Inch: 3.5 x 5.4 x 3.6 mm: 88 x 137 x 92
Weight:	6 oz. (170 Grams)
Construction:	Machined Delrin and Aluminum
Sensor Connector:	Fischer 5 Pin
Pan Rotation:	360°
Tilt Movement:	180°
Pan and Tilt Lock:	Twist Lock Knob (2)
Mounting Hole:	1/4-20 Threaded
Mounting Stud:	3/8-16 Threaded
Mounting Diameter:	5/8 inch, 15 mm, 19 mm