

| | Units | 18mm | 21mm | 25mm | 32mm | 40mm | 50mm | 65mm | 75mm | 100mm | 135mm |
|--|--------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|---------------|
| T Stop Range | | T2.8 -22 | T2.8 -22 | T2.8 -22 | T2.8 -22 | T2.8 -22 | T2.8 -22 | T2.8 -22 | T2.8 -22 | T2.8 -22 | T2.8 -22 |
| Angular Rotation of Iris Scale | Degrees | 77 | 77 | 77 | 77 | 77 | 77 | 77 | 77 | 77 | 96 |
| Minimum Marked Object Distance | mm inches | 250 10 | 250 10 | 250 10 | 300 12 | 440 16 | 500 20 | 700 27 | 750 30 | 900 36 | 1000 39 |
| Close Focus from Lens Front | mm inches | 80 3 | 80 3 | 93 4 | 139 5 | 240 9.5 | 311 12 | 500 20 | 564 22 | 711 28 | 790 31 |
| Angular Rotation to MOD Endstop | Degrees | 300 | 300 | 300 | 300 | 300 | 300 | 300 | 300 | 300 | 300 |
| Maximum Diagonal Angle for S35 Format | Degrees | 80 | 73 | 62 | 50 | 41 | 34 | 26 | 22 | 17 | 14.16 |
| Length from Front of Lens to Lens Mount | mm inches | 120 4.72 | 110 4.33 | 106 4.17 | 110 4.33 | 110 4.33 | 137 5.39 | 135 5.32 | 137 5.39 | 137 5.39 | 157.8 6.21 |
| Maximum Front Diameter | mm inches | 110 4.33 | 87 3.43 | 87 3.43 | 87 3.43 | 87 3.43 | 87 3.43 | 87 3.43 | 87 3.43 | 87 3.43 | 87 3.43 |
| Total Weight | kg lbs | 1.3 2.9 | 1.6 3.4 | 1.4 3.0 | 1.6 3.5 | 1.7 3.7 | 1.5 3.3 | 1.6 3.5 | 1.6 3.5 | 1.6 3.5 | 1.8 4.0 |

Max Format Covered 33.54mm Diagonal

Focus Scales Two opposing focus scales – metric or footage. Scales marked from infinity to MOD

Focus Drive Gear 121 teeth 0.8 metric module x 5.0mm wide x 101mm from the image plane

Iris Scales Two opposing linear T scales – whole and third stops marked

Iris Drive Gear 119 teeth 0.8 metric module x 2.5mm wide x 85mm from image plane

Screw-In Filter M82 x 0.75 (25mm - 135mm)

Compatibility All Cooke miniS4/i primes, except 18mm, have a common fixed front diameter of 87mm, with a focus drive gear of 121T x 0.8 mod and an iris drive gear of 119T x 0.8.