



Fixture Specifications

Fixture	Part Number	Lamps	Lamp Type	Dimensions	Weight w/Lamps
Flathead 80	CFX-4808	8	F75 / T12	51 x 24 x 4" (129.5 x 61 x 10cm)	27lb (12kg)

Ballast Specifications

Ballast	Part Number	Input Voltage	Output Frequency	Amperage	Lamp Switching	Output Switching	Dimensions	Weight
4Bank (x2)	BAL-427-120U	100~240VAC 50/60Hz	25kHz	2 x 2.6A=5.2A	1~4	4ft/2ft	13 x 9.5 x 3" (33 x 24 x 7.6cm)	4.9 lb (2.2kg)
4Bank (x2)	BAL-427-230U	240~100VAC 50/60Hz	25kHz	2 x 1.4A=2.8A	1~4	4ft/2ft	13 x 9.5 x 3" (33 x 24 x 7.6cm)	4.9 lb (2.2kg)
4Bank DMX (x2)	BAL-457-120U	100~240VAC 50/60Hz	25kHz	2 x 2.6A=5.2A	1~4	4ft/2ft	12 x 11 x 3" (30.5 x 28 x 7.6cm)	5.3 lb (2.4kg)
4Bank DMX (x2)	BAL-457-230U	240~100VAC 50/60Hz	25kHz	2 x 1.4A=2.8A	1~4	4ft/2ft	12 x 11 x 3" (30.5 x 28 x 7.6 cm)	5.3 lb (2.4kg)

▼ Photometrics

Flathead 80	FC	930	325	160	94	61	44	33	26	20	17
	Feet	2	4	6	8	10	12	14	16	18	20
	LUX	12490	4748	2412	1443	958	678	505	394	320	265
	Meters	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5

Photometrics 200 ASA@125th/sec shutter

	Feet	2ft	4ft	6ft	8ft	10ft
Flathead 80	F-stop	5.6/8	4.0/3	2.8/3	2.0/6	2.0
	FC	930	325	160	94	61
	Meters	0.5	1	1.5	2	2.5
Flathead 80	F-stop	8.0/2	4.0/8	2.8/8	2.8/1	2.0/5
	LUX	12490	4748	2412	1443	958