



## Technical Data

Supreme Prime	Release	Aperture	Close Focus <sup>1</sup>	Length <sup>2</sup>	Front diameter	Weight	Horizontal Angle of View	
							Full-Frame <sup>3</sup>	Super 35 <sup>4</sup>
15 mm T1.8	2020	T1.8 to T22	tbd	tbd	114 mm / 4.5"	tbd	tbd	tbd
18 mm T1.5	2020	T1.5 to T22	tbd	163 mm   6.4"	114 mm / 4.5"	tbd	tbd	tbd
21 mm T1.5	Shipping	T1.5 to T22	0.35 m / 13.7"	119 mm / 4.7"	95 mm / 3.7"	1.61 kg / 3.55 lbs	79.5°	59.8°
25 mm T1.5	Shipping	T1.5 to T22	0.26 m / 10"	119 mm / 4.7"	95 mm / 3.7"	1.42 kg / 3.13 lbs	70.8°	52.3°
29 mm T1.5	Shipping	T1.5 to T22	0.33 m / 13"	121 mm / 4.8"	95 mm / 3.7"	1.61 kg / 3.55 lbs	64°	46.8°
35 mm T1.5	Shipping	T1.5 to T22	0.32 m / 13"	119 mm / 4.7"	95 mm / 3.7"	1.40 kg / 3.09 lbs	55°	39.6°
50 mm T1.5	Shipping	T1.5 to T22	0.45 m / 18"	119 mm / 4.7"	95 mm / 3.7"	1.22 kg / 2.69 lbs	39°	27.5°
65 mm T1.5	Shipping	T1.5 to T22	0.6 m / 2'	121 mm / 4.8"	95 mm / 3.7"	1.63 kg / 3.59 lbs	30.5°	21.3°
85 mm T1.5	Shipping	T1.5 to T22	0.84 m / 2'9"	119 mm / 4.7"	95 mm / 3.7"	1.42 kg / 3.13 lbs	24°	16.7°
100 mm T1.5	Shipping	T1.5 to T22	1.1 m / 3'9"	119 mm / 4.7"	95 mm / 3.7"	1.70 kg / 3.74 lbs	20.4°	14.2°
135 mm T1.5	Shipping	T1.5 to T22	1.35 m / 4'5"	146 mm / 5.7"	114 mm / 4.5"	2.27 kg / 5.00 lbs	15.6°	10.9°
150 mm T1.8	Q4 2019	T1.8 to T22	1.5 m / 4'11"	146 mm / 5.7"	114 mm / 4.5"	2.27 kg / 5.00 lbs	13.7°	9.5°
200 mm T2.2	2020	T2.2 to T22	2 m   6'7"	183 mm   7.2"	114 mm / 4.5"	tbd	6.28°	4.76°

<sup>1</sup> Close focus distance is measured from the image plane

<sup>2</sup> Front to PL mount flange

<sup>3</sup> Horizontal angle of view for a full-frame camera (aspect ratio 1:1.5, dimensions 36 mm x 24 mm / 1.42" x 0.94")

<sup>4</sup> Horizontal angle of view for an ANSI Super 35 Silent camera (aspect ratio 1:1.33, dimensions 24.9 mm x 18.7 mm / 0.98" x 0.74")